

Wellhead Wireline Pressure Control Equipment



Item	Model	Bore Size		Working Pressure		Temp. Class	Material Class	PSL Level	Note
		in	mm	MPa	psi				
1	FP65-35	2-9/16	65	35	5000	-46℃ ~ 121℃ -50°F ~ 250°F L~U	EE FF HH	PSL3 ~ PSL4	Typical wireline pressure control equipment string including: 1. Wellhead Adapter Flange 2. Pump-in Sub 3. Wireline valve(BOP) 4. Quick Test Sub 5. Tool Trap 6. Lubricator 7. Tool Catcher 8. Grease Injection Head 9. Stuffing Box 10. Line Wiper 11. Grease Injection Unit ▲We can supply following customer specification. ▲ Meeting Spec API 6A, NACE MR0175
2	FP65-70	2-9/16	65	70	10000				
3	FP65-105	2-9/16	65	105	15000				
4	FP76-35	3	76	35	5000				
5	FP76-70	3	76	70	10000				
6	FP76-105	3	76	105	15000				
7	FP102-35	4	102	35	5000				
8	FP102-70	4	102	70	10000				
9	FP102-105	4	102	105	15000				
10	FP102-140	4	102	140	20000				
11	FP127-35	5	127	35	5000				
12	FP127-70	5	127	70	10000				
13	FP127-105	5	127	105	15000				
14	FP140-35	5-1/2	140	35	5000				
15	FP140-70	5-1/2	140	70	10000				
16	FP140-105	5-1/2	140	105	15000				
17	FP160-35	6-3/8	160	35	5000				
18	FP160-70	6-3/8	160	70	10000				
19	FP160-105	6-3/8	160	105	15000				
20	FP180-35	7-1/16	180	35	5000				
21	FP180-70	7-1/16	180	70	10000				
22	FP180-105	7-1/16	180	105	15000				